



MEDIUM VOLTAGE AC DRIVES

ABB general purpose drives

ACS580MV – 200 to 6300 kW
6 to 11 kV



What does all-compatible mean for you?

The idea behind all-compatible is simple: the better a drive fits to your processes, users and business and environmental goals, the faster you start enjoying the benefits it brings. The ACS580MV is part of the allcompatible drive portfolio with other drives complementing the offering. The drives share the same architecture and user interfaces, yet there is an optimal drive for virtually any application.

During drive selection, you save time as the drives have many built-in features facilitating the selection process. The simplicity carries on to the drive set up and commissioning. With a user-friendly control panel and state-of-the-art drive design, installation and operation is made easy and optimal.

The total cost of ownership and your impact on the environment is lower with the drives ensuring your processes run efficiently and reliably. The user interfaces and tools enable you to monitor and analyze the drives. Advanced diagnostics ensure highest reliability and a trouble free operation by quickly detecting problems and giving instructions for resolving them. As a result, you can fine-tune the application to get more out of the drives and process using less energy.

Once you have used one all-compatible drive, you can use them all. Your knowledge accumulates with each new installation, resulting in more efficient processes and business.

That's it. In short, all-compatible means better business sense.

Table of contents


04–05	The all-compatible ACS580MV general purpose drive
06–07	Switch on simplicity without trading off efficiency
08	Human all-compatible
09	Process all-compatible
10	Environment all-compatible
11	Business all-compatible
12	The reliable drive for a broad range of applications
13	How to select a drive
14	Technical data
15	Dimensions
16–17	Ratings, types and voltages
18–19	Standard interface and extensions for plug-in connectivity
20	Standard software with versatile features
21	Easy drive operation with Bluetooth control panel
22	PC tools for drive commissioning and process tuning capabilities
23	Flexible connectivity to automation networks
24	Input/output extension modules for increased connectivity
24	Cabinet options
24	Cooling
25	Safety features
25	Manual bypass feature
25	Specialities
26–27	Taking care of your drives, caring about your business
28–29	A lifetime of peak performance

The all-compatible ACS580MV general purpose drive

The ACS580MV is part of the all-compatible ABB drive portfolio. It turns complicated to simple while ensuring highest reliability.

The drive controls a wide range of applications in different industries, and yet it requires very

little setting up or commissioning. All the essential features are built-in as standard, which reduces the need for additional hardware and simplifies drive selection. The drive is easy to use in terms of controlling various applications, such as pumps and fans.



What if you have other requirements? You can select another member of the all-compatible drives portfolio. The drives share the same user interfaces and options, enabling you to use

the knowledge you have gained with the ACS580MV drives. You increasingly keep saving time, and saving time in business means saving money.



Switch on simplicity without trading off efficiency

The ACS580MV series general purpose drives are part of ABB's all-compatible drives portfolio. They promise you reliability and efficiency throughout their whole life cycle.

Simple to operate, safe to use

The standardized interface for fieldbus, I/O's, cable entry and breaker control in combination with emergency off and emergency stop functions ensure easy and safe drive operation.



Wireless monitoring via Bluetooth

Bluetooth control panel enables you to easily monitor your drive operation status and fault diagnostics with your mobile devices.

Boosting energy efficiency

Energy efficiency information helps you monitor and save the energy used in your process.



The drive is easy to select, install and use. Build-in assistant functionality is helpful to easily operate and maintain the drive.

**Monitoring and maintenance tool**

Drive composer PC tool for configuration, monitoring and process tuning. PC tool is connected to the drive's control panel via USB or Ethernet interface.

Communication with all major automation networks

Fieldbus adapters enable connectivity with all major industrial automation networks.

Performance-based reliability

Advanced diagnostics and warning system enables users to effectively analyze and resolve issues. The power loss ride-through function of the ACS580MV drive ensure reliable and trouble free operation as well as high robustness against weak network performance.

Human all-compatible

When using an all-compatible drive, you don't have to know all the parameters or use any programming language. Your own mother tongue and common sense is enough. Straightforward settings menu and assistants help you to operate the drive easily.

The Drive composer PC tool provides extensive drive monitoring and process tuning capabilities. The integrated emergency off and emergency stop function ensures high safety for machine operators.

If your process requirements grow, the next all-compatible drive will also have the same interface, look & feel and have the tools, providing you with flexibility without adding complexity.

Learn it once, use it everywhere – simple and flexible drive operation helps you save time and money.




Process all-compatible

The ACS580MV drives are ready for a broad range of standard drive applications, and all essential features for general purpose speed and torque control applications are built-in as standard.

The power range reaches up to 6.3 MW. The various fieldbus adapter options allow communication with all of the major industrial automation networks.

For applications with different requirements the common drives architecture enables the smooth transition to other all-compatible drives in the ABB portfolio, such as the ACS580 general purpose drive or the ACS880 industrial drive.



What do we mean by communication compatibility?
Exactly what it says. You can easily connect the drive to all major automation networks.

Environment all-compatible

With ABB and the all-compatible drives you are not only optimizing the energy consumption of an electric motor but also your whole process.

The drive itself helps you to use only the exact amount of energy needed to run your motor. The built-in energy efficiency calculators help you to analyze and optimize processes. With the help of our life cycle services, you will be able to keep your process running reliably and efficiently throughout the life cycle of the drives.

The greenest energy is the energy that you do not use.
That is what the ACS580MV allows you to do.



Business all-compatible


Usually, any drive is a justified investment that gives a short payback time by lowering energy consumption and helping to improve productivity of the processes.

When you choose an all-compatible drive from ABB, you get more than just a drive. You get our wide range of products and services to support your business, including our decades of experience in various industries. ABB's local offices and global value provider network members will be near to you.



Mature technology inside, the whole ABB outside, designed to support your business.

The reliable drive for a broad range of applications



The cabinet-built ACS580MV general purpose drive is designed to control pumps, fans, and many other applications like compressors as well as for process control in different industries. The drive is equipped with various features that simplify ordering and delivery, and reduces commissioning costs since everything is provided in a compact package.

All essential features for reliable operations

The drive features a new generation of cascaded h-bridge technology which, together with the drive's design, provides superior mitigation of harmonics in a compact design. Other built-in features like power loss ride-through ensures reliable and trouble free operation as well as high robustness against weak network performance. Features like IP42, redundant cooling fans and an advanced preventive warning system ensure highest reliability even in harsh industrial environments. The plug-in fieldbus adapter modules enable connectivity with all major automation systems. Other options like manual bypass provide high quality features for targeted industries and applications. The drive and all options have coated boards as standard improving durability in rough surrounding conditions.

Easy to use control panel and PC tool

The control panel and PC tool provide effective drive operation, monitoring and maintenance. The control panel's straightforward settings menu and many built-in assistants ensure easy usage while the Drive composer PC tool offers extensive drive monitoring and process tuning capabilities.

ACS580MV goes digital

The drive has a Bluetooth panel enabling easy connection to mobile devices for wireless commissioning and monitoring.

Remote assistance and condition monitoring are also available. In case of a problem, ABB expert provides rapid support. Condition monitoring helps to anticipate possible faults, operational issues and maintenance needs.

Boosting energy efficiency

The built-in energy efficiency calculators, including used and saved kWh, CO₂ reduction and money saved, help users finetune processes to ensure optimal energy use.

How to select a drive

It is very easy to select the right drive.

Start with identifying your motor voltage. This tells you what rating table to use. The ACS580MV currently supports voltage supply from 6 to 11 kV. See pages 16 and 17.

Select your drive's ordering code from the rating table based on your motor's nominal power rating.

Choose your motor's nominal power rating from the ratings tables on pages 16 and 17.

16

AEM MEDIUM VOLTAGE AC BRIVIS, ACBUSHY, CATALO

Ratings, types and voltages

Standard AC BV

AC-BV 0.6/1.0 type (standard) are valid as nominal standard voltage 0.6 kV

Type designation		Pole size		
P_1	P_2	P_1	P_2	
200	248	0001	ACBUSHY-07-0001A-000	0.01
200	248	0002	ACBUSHY-07-0002A-000	0.02
240	285	0001	ACBUSHY-07-0001A-000	0.01
240	285	0002	ACBUSHY-07-0002A-000	0.02
315	412	0001	ACBUSHY-07-0001A-000	0.01
315	412	0002	ACBUSHY-07-0002A-000	0.02
400	456	0001	ACBUSHY-07-0001A-000	0.01
400	456	0002	ACBUSHY-07-0002A-000	0.02
500	571	0004	ACBUSHY-07-0004A-000	0.04
540	715	0077	ACBUSHY-07-0007A-000	0.07
540	715	0084	ACBUSHY-07-0008A-000	0.08
710	842	0084	ACBUSHY-07-0008A-000	0.08
800	1071	0106	ACBUSHY-07-0010A-000	0.10
900	1097	0107	ACBUSHY-07-0010A-000	0.10
1000	1141	0122	ACBUSHY-07-0012A-000	0.12
1100	1150	0127	ACBUSHY-07-0012A-000	0.12
1250	1276	0135	ACBUSHY-07-0013A-000	0.14
1400	1417	0155	ACBUSHY-07-0015A-000	0.15
1600	1616	0191	ACBUSHY-07-0019A-000	0.17
2000	2048	0249	ACBUSHY-07-0024A-000	0.25
2500	2587	0313	ACBUSHY-07-0031A-000	0.32
3000	3175	0391	ACBUSHY-07-0039A-000	0.40
3500	3715	0456	ACBUSHY-07-0045A-000	0.48
4000	4274	0544	ACBUSHY-07-0054A-000	0.56
5500	5761	0681	ACBUSHY-07-0068A-000	0.68

Other ratings like 0.3 kV or 0.6 kV are possible

Standard AC BV

AC-BV 0.6/1.0 type (standard) are valid as nominal standard voltage 0.6 kV

Type designation		Pole size		
P_1	P_2	P_1	P_2	
200	248	0001	ACBUSHY-07-0001A-000	0.01
200	248	0002	ACBUSHY-07-0002A-000	0.02
240	285	0001	ACBUSHY-07-0001A-000	0.01
240	285	0002	ACBUSHY-07-0002A-000	0.02
315	412	0001	ACBUSHY-07-0001A-000	0.01
315	412	0002	ACBUSHY-07-0002A-000	0.02
400	456	0001	ACBUSHY-07-0001A-000	0.01
400	456	0002	ACBUSHY-07-0002A-000	0.02
500	571	0004	ACBUSHY-07-0004A-000	0.04
540	715	0077	ACBUSHY-07-0007A-000	0.07
540	715	0084	ACBUSHY-07-0008A-000	0.08
710	842	0084	ACBUSHY-07-0008A-000	0.08
800	1071	0106	ACBUSHY-07-0010A-000	0.10
900	1097	0107	ACBUSHY-07-0010A-000	0.10
1000	1141	0122	ACBUSHY-07-0012A-000	0.12
1100	1150	0127	ACBUSHY-07-0012A-000	0.12
1250	1276	0135	ACBUSHY-07-0013A-000	0.14
1400	1417	0155	ACBUSHY-07-0015A-000	0.15
1600	1616	0191	ACBUSHY-07-0019A-000	0.17
2000	2048	0249	ACBUSHY-07-0024A-000	0.25
2500	2587	0313	ACBUSHY-07-0031A-000	0.32
3000	3175	0391	ACBUSHY-07-0039A-000	0.40
3500	3715	0456	ACBUSHY-07-0045A-000	0.48
4000	4274	0544	ACBUSHY-07-0054A-000	0.56
5500	5761	0681	ACBUSHY-07-0068A-000	0.68

Neutral Rating

ACBUSHY-07-0001A-000 is valid as nominal voltage 0.6 kV

Continuous current rating up to 63 A, allowing 100% I_n for 4 hours 30 min

Page 16

Choose your options and spare part package according to your preference (on pages 23, 24 and 25).

RATINGS, TYPES AND VOLTAGES

17

ACBULB 100W

ACBULB 100W power ratings are valid at nominal voltage 230 V

I_{a}	I_{b}	I_{c}	I_{a}	I_{b}	I_{c}
225	350	350	ACBULB001-0003A-010	0381	
225	350	350	ACBULB001-0003A-010	0382	
225	350	350	ACBULB001-0003A-010	0383	
225	350	350	ACBULB001-0003A-010	0384	
420	640	640	ACBULB001-0004A-010	0385	
420	640	640	ACBULB001-0004A-010	0386	
420	640	640	ACBULB001-0004A-010	0387	
420	640	640	ACBULB001-0004A-010	0388	
720	1070	1070	ACBULB001-0007A-010	0389	
720	1070	1070	ACBULB001-0007A-010	0390	
720	1070	1070	ACBULB001-0007A-010	0391	
720	1070	1070	ACBULB001-0007A-010	0392	
1050	1540	1540	ACBULB001-0010A-010	0393	
1050	1540	1540	ACBULB001-0010A-010	0394	
1050	1540	1540	ACBULB001-0010A-010	0395	
1050	1540	1540	ACBULB001-0010A-010	0396	
1500	2370	2370	ACBULB001-0015A-010	0397	
1500	2370	2370	ACBULB001-0015A-010	0398	
1500	2370	2370	ACBULB001-0015A-010	0399	
1500	2370	2370	ACBULB001-0015A-010	0400	
2000	3160	3160	ACBULB001-0020A-010	0401	
2000	3160	3160	ACBULB001-0020A-010	0402	
2000	3160	3160	ACBULB001-0020A-010	0403	
2000	3160	3160	ACBULB001-0020A-010	0404	
2000	3160	3160	ACBULB001-0020A-010	0405	
2000	3160	3160	ACBULB001-0020A-010	0406	
2000	3160	3160	ACBULB001-0020A-010	0407	
2000	3160	3160	ACBULB001-0020A-010	0408	
2000	3160	3160	ACBULB001-0020A-010	0409	
2000	3160	3160	ACBULB001-0020A-010	0410	
2000	3160	3160	ACBULB001-0020A-010	0411	
2000	3160	3160	ACBULB001-0020A-010	0412	
2000	3160	3160	ACBULB001-0020A-010	0413	
2000	3160	3160	ACBULB001-0020A-010	0414	
2000	3160	3160	ACBULB001-0020A-010	0415	
2000	3160	3160	ACBULB001-0020A-010	0416	
2000	3160	3160	ACBULB001-0020A-010	0417	
2000	3160	3160	ACBULB001-0020A-010	0418	
2000	3160	3160	ACBULB001-0020A-010	0419	
2000	3160	3160	ACBULB001-0020A-010	0420	
2000	3160	3160	ACBULB001-0020A-010	0421	
2000	3160	3160	ACBULB001-0020A-010	0422	
2000	3160	3160	ACBULB001-0020A-010	0423	
2000	3160	3160	ACBULB001-0020A-010	0424	
2000	3160	3160	ACBULB001-0020A-010	0425	
2000	3160	3160	ACBULB001-0020A-010	0426	
2000	3160	3160	ACBULB001-0020A-010	0427	
2000	3160	3160	ACBULB001-0020A-010	0428	
2000	3160	3160	ACBULB001-0020A-010	0429	
2000	3160	3160	ACBULB001-0020A-010	0430	
2000	3160	3160	ACBULB001-0020A-010	0431	
2000	3160	3160	ACBULB001-0020A-010	0432	
2000	3160	3160	ACBULB001-0020A-010	0433	
2000	3160	3160	ACBULB001-0020A-010	0434	
2000	3160	3160	ACBULB001-0020A-010	0435	
2000	3160	3160	ACBULB001-0020A-010	0436	
2000	3160	3160	ACBULB001-0020A-010	0437	
2000	3160	3160	ACBULB001-0020A-010	0438	
2000	3160	3160	ACBULB001-0020A-010	0439	
2000	3160	3160	ACBULB001-0020A-010	0440	
2000	3160	3160	ACBULB001-0020A-010	0441	
2000	3160	3160	ACBULB001-0020A-010	0442	
2000	3160	3160	ACBULB001-0020A-010	0443	
2000	3160	3160	ACBULB001-0020A-010	0444	
2000	3160	3160	ACBULB001-0020A-010	0445	
2000	3160	3160	ACBULB001-0020A-010	0446	
2000	3160	3160	ACBULB001-0020A-010	0447	
2000	3160	3160	ACBULB001-0020A-010	0448	
2000	3160	3160	ACBULB001-0020A-010	0449	
2000	3160	3160	ACBULB001-0020A-010	0450	
2000	3160	3160	ACBULB001-0020A-010	0451	
2000	3160	3160	ACBULB001-0020A-010	0452	
2000	3160	3160	ACBULB001-0020A-010	0453	
2000	3160	3160	ACBULB001-0020A-010	0454	
2000	3160	3160	ACBULB001-0020A-010	0455	
2000	3160	3160	ACBULB001-0020A-010	0456	
2000	3160	3160	ACBULB001-0020A-010	0457	
2000	3160	3160	ACBULB001-0020A-010	0458	
2000	3160	3160	ACBULB001-0020A-010	0459	
2000	3160	3160	ACBULB001-0020A-010	0460	
2000	3160	3160	ACBULB001-0020A-010	0461	
2000	3160	3160	ACBULB001-0020A-010	0462	
2000	3160	3160	ACBULB001-0020A-010	0463	
2000	3160	3160	ACBULB001-0020A-010	0464	
2000	3160	3160	ACBULB001-0020A-010	0465	
2000	3160	3160	ACBULB001-0020A-010	0466	
2000	3160	3160	ACBULB001-0020A-010	0467	
2000	3160	3160	ACBULB001-0020A-010	0468	
2000	3160	3160	ACBULB001-0020A-010	0469	
2000	3160	3160	ACBULB001-0020A-010	0470	
2000	3160	3160	ACBULB001-0020A-010	0471	
2000	3160	3160	ACBULB001-0020A-010	0472	
2000	3160	3160	ACBULB001-0020A-010	0473	
2000	3160	3160	ACBULB001-0020A-010	0474	
2000	3160	3160	ACBULB001-0020A-010	0475	
2000	3160	3160	ACBULB001-0020A-010	0476	
2000	3160	3160	ACBULB001-0020A-010	0477	
2000	3160	3160	ACBULB001-0020A-010	0478	
2000	3160	3160	ACBULB001-0020A-010	0479	
2000	3160	3160	ACBULB001-0020A-010	0480	
2000	3160	3160	ACBULB001-0020A-010	0481	
2000	3160	3160	ACBULB001-0020A-010	0482	
2000	3160	3160	ACBULB001-0020A-010	0483	
2000	3160	3160	ACBULB001-0020A-010	0484	
2000	3160	3160	ACBULB001-0020A-010	0485	
2000	3160	3160	ACBULB001-0020A-010	0486	
2000	3160	3160	ACBULB001-0020A-010	0487	
2000	3160	3160	ACBULB001-0020A-010	0488	
2000	3160	3160	ACBULB001-0020A-010	0489	
2000	3160	3160	ACBULB001-0020A-010	0490	
2000	3160	3160	ACBULB001-0020A-010	0491	
2000	3160	3160	ACBULB001-0020A-010	0492	
2000	3160	3160	ACBULB001-0020A-010	0493	
2000	3160	3160	ACBULB001-0020A-010	0494	
2000	3160	3160	ACBULB001-0020A-010	0495	
2000	3160	3160	ACBULB001-0020A-010	0496	
2000	3160	3160	ACBULB001-0020A-010	0497	
2000	3160	3160	ACBULB001-0020A-010	0498	
2000	3160	3160	ACBULB001-0020A-010	0499	
2000	3160	3160	ACBULB001-0020A-010	0500	
2000	3160	3160	ACBULB001-0020A-010	0501	
2000	3160	3160	ACBULB001-0020A-010	0502	
2000	3160	3160	ACBULB001-0020A-010	0503	
2000	3160	3160	ACBULB001-0020A-010	0504	
2000	3160	3160	ACBULB001-0020A-010	0505	
2000	3160	3160	ACBULB001-0020A-010	0506	
2000	3160	3160	ACBULB001-0020A-010	0507	
2000	3160	3160	ACBULB001-0020A-010	0508	
2000	3160	3160	ACBULB001-0020A-010	0509	
2000	3160	3160	ACBULB001-0020A-010	0510	
2000	3160	3160	ACBULB001-0020A-010	0511	
2000	3160	3160	ACBULB001-0020A-010	0512	
2000	3160	3160	ACBULB001-0020A-010	0513	
2000	3160	3160	ACBULB001-0020A-010	0514	
2000	3160	3160	ACBULB001-0020A-010	0515	
2000	3160	3160	ACBULB001-0020A-010	0516	
2000	3160	3160	ACBULB001-0020A-010	0517	
2000	3160	3160	ACBULB001-0020A-010	0518	
2000	3160	3160	ACBULB001-0020A-010	0519	
2000	3160	3160	ACBULB001-0020A-010	0520	
2000	3160	3160	ACBULB001-0020A-010	0521	
2000	3160	3160	ACBULB001-0020A-010	0522	
2000	3160	3160	ACBULB001-0020A-010	0523	
2000	3160	3160	ACBULB001-0020A-010	0524	
2000	3160	3160	ACBULB001-0020A-010	0525	
2000	3160	3160	ACBULB001-0020A-010	0526	
2000	3160	3160	ACBULB001-0020A-010	0527	
2000	3160	3160	ACBULB001-0020A-010	0528	
2000	3160	3160	ACBULB001-0020A-010	0529	
2000	3160	3160	ACBULB001-0020A-010	0530	
2000	3160	3160	ACBULB001-0020A-010	0531	
2000	3160	3160	ACBULB001-0020A-010	0532	
2000	3160	3160	ACBULB001-0020A-010	0533	
2000	3160	3160	ACBULB001-0020A-010	0534	
2000	3160	3160	ACBULB001-0020A-010	0535	
2000	3160	3160	ACBULB001-0020A-010	0536	
2000	3160	3160	ACBULB001-0020A-010	0537	
2000	3160	3160	ACBULB001-0020A-010	0538	
2000	3160	3160	ACBULB001-0020A-010	0539	
2000	3160	3160	ACBULB001-0020A-010	0540	
2000	3160	3160	ACBULB001-0020A-010	0541	
2000	3160	3160	ACBULB001-0020A-010	0542	
2000	3160	3160	ACBULB001-0020A-010	0543	
2000	3160	3160	ACBULB001-0020A-010	0544	
2000	3160	3160	ACBULB001-0020A-010	0545	
2000	3160	3160	ACBULB001-0020A-010	0546	
2000	3160	3160	ACBULB001-0020A-010	0547	
2000	3160	3160	ACBULB001-0020A-010	0548	
2000	3160	3160	ACBULB001-0020A-010	0549	
2000	3160	3160	ACBULB001-0020A-010	0550	
2000	3160	3160	ACBULB001-0020A-010	0551	
2000	3160	3160	ACBULB001-0020A-010	0552	
2000	3160	3160	ACBULB001-0020A-010	0553	
2000	3160	3160	ACBULB001-0020A-010	0554	
2000	3160	3160	ACBULB001-0020A-010	0555	
2000	3160	3160	ACBULB001-0020A-010	0556	
2000	3160	3160	ACBULB001-0020A-010	0557	
2000	3160	3160	ACBULB001-0020A-010	0558	
2000	3160				

Page 17

Flexible connectivity to automation networks

A fieldbus enables communication between drives and PLC systems, I/O devices and the process. Fieldbus communication reduces wiring costs when compared with traditional hard-wired input/output connections. Fieldbus systems also offer the ability to gather large amounts of data.

Cabling
Substituting the large amount of conventional drive control cabling and wiring with a single cable reduces costs and increases system reliability and flexibility.

Design
The use of fieldbus control reduces engineering time at installation due to the modular structure of the hardware and software and the simplicity of the connections to the drives.

The general purpose drives are compatible with a wide range of fieldbus protocols. The optional plug-in fieldbus adapter modules can easily be mounted inside the drive.

The benefits of fieldbus communication are described below:

Drive monitoring
A set of drive parameters and/or actual signals such as torque, speed, current, etc., can be selected for cyclic data transfer, providing a data stream.

Drive diagnostics
Accurate and reliable diagnostic information can be obtained through the alarm, limit and fault words, giving easy interfacing with micrologic MMIC.

Universal communication with ABB fieldbus adapters

Fieldbus Adapter	Options
...	...

Modbus adapter	PSCA
Ethernet adapter (SIP, Modbus/TCP, PROFINET)	FEN

Type designation:	ACS580MV	-	07	-	0143A	-	100
Product series							
Construction							
Rating							
Voltage							

Page 23



Technical data

Main connection	
Voltage	6 to 11 kV \pm 10%, (-25% with reduced power)
Power range	6 kV: 200 to 3550 kW / 6.3 kV: 200 to 3500 kW / 6.6 kV: 200 to 4000 kW 10 kV: 200 to 5600 kW / 10.5 kV: 200 to 6300 kW / 11 kV: 200 to 6300 kW
Supply frequency	50/60 Hz \pm 5%
Power factor	$\cos\varphi \geq 0.96$
Drive system efficiency (at nominal power)	> 96% (Including transformer and auxiliary losses)
Motor connection	
Voltage	6 to 11 kV
Frequency	0 to 120 Hz output, up to 80 Hz nominal motor frequency
Motor control	Scalar and vector control
Torque control	Torque step rise time: < 10 ms with nominal torque, Non-linearity: \pm 5% with nominal torque
Speed control	Static accuracy: 20% of motor nominal slip Dynamic accuracy: 1% seconds with 100% torque step
Overload	110% (1 min/10 min at 40 °C)
Maximum motor cable length	1000 m
Output current THD	< 2%
Product compliance	
CE	
GOST-R	
Adjustable speed electrical power drive systems: EMC, IEC 61800-3: (2004+A1:2011, edition 2.1) 2012	
Adjustable speed electrical power drive systems: General requirements, IEC 61800-4: 2002	
Adjustable speed electrical power drive systems: Safety requirements, IEC 61800-5-1: 2007	
Adjustable speed electrical power drive systems: Safety requirements, IEC 61800-5-2: 2007	
Safety of machinery – Electrical equipment of machines: General requirements, IEC 60204-1: 2005	
Safety of machinery – Electrical equipment of machines: Requirements for HV equipment, IEC 60204-11: 2000	
Recommended Practices and Requirements for Harmonic Control in Electrical Power Systems, IEEE 519-1992	
EU RoHS directive 2011/65/EU	
EMC	
According to IEC 61000-2-4: 2002 Class 2; IEC 61800-3: 2012 Category 4	
Environmental limits	
Ambient temperature	
Storage	-40 to +70 °C
Transport	-40 to +70 °C
Operation	0 to +40 °C, no frost allowed > 40 °C, with derating
Cooling method	
Air-cooled	Dry clean air
Altitude	
To 2,000 m	Without derating
Above 2,000 m	Please contact ABB
Relative humidity	5 to 95 %, no condensation allowed
Degree of protection	IP21 as standard, IP42 as an optional variant
Contamination levels	No conductive dust allowed
Storage (excl. UPS)	IEC60721-3-1 1K22 / 1Z3 / 1B1 / 1M3
Transportation (excl. UPS)	IEC60721-3-2 2K12 / 2B1 / 2M4
Operation	IEC60721-3-3 3K3 / 3B1 / 3C2 / 3S2 / 3M3

Dimensions

Voltage class 6 / 6.3 kV

Frame size	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
6R1	2571	4030	1176	2900
6R2	2571	4030	1176	3100
6R3	2571	4030	1176	3500
6R4	2571	4030	1176	4000
6R5	2571	4030	1176	4600
6R6	2571	4230	1176	5000
6R7	2571	5630	1376	7100
6R8	2571	5630	1376	8800
6R9	2571	6230	1376	10300

Voltage class 6.6 kV

Frame size	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
6.6R1	2571	4030	1176	3000
6.6R2	2571	4030	1176	3300
6.6R3	2571	4030	1176	3700
6.6R4	2571	4030	1176	4300
6.6R5	2571	4030	1176	4800
6.6R6	2571	4230	1176	5600
6.6R7	2571	6030	1376	7800
6.6R8	2571	6230	1376	9500
6.6R9	2571	6630	1376	11350

Voltage class 10 kV

Frame size	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
10R1	2571	4030	1176	3300
10R2	2571	4030	1176	3700
10R3	2571	4030	1176	4400
10R4	2571	4430	1176	5100
10R5	2571	4630	1176	5900
10R6	2571	4630	1176	6600
10R7	2571	6630	1376	10100
10R8	2571	7030	1376	12300
10R9	2871	7030	1376	14600

Voltage class 10.5 / 11 kV

Frame size	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
11R1	2571	4030	1176	3500
11R2	2571	4030	1176	4000
11R3	2571	4030	1176	4400
11R4	2571	4630	1176	5600
11R5	2571	4630	1176	6000
11R6	2571	4630	1176	7200
11R7	2571	7430	1376	11200
11R8	2571	7830	1376	13400
11R9	2871	7830	1376	16100

Ratings, types and voltages

Load profile 6 kV					
$U_N = 6 \text{ kV}$. The power ratings are valid at nominal voltage 6 kV.					
Normal use			Type designation	Frame size	
P_N (kW)	P_N (hp)	I_{2N} (A)			
200	268	0026	ACS580MV-07-0026A-060	6R1	
225	302	0030	ACS580MV-07-0030A-060	6R2	
250	335	0034	ACS580MV-07-0034A-060	6R2	
280	375	0038	ACS580MV-07-0038A-060	6R2	
315	422	0040	ACS580MV-07-0040A-060	6R2	
355	476	0049	ACS580MV-07-0049A-060	6R3	
400	536	0051	ACS580MV-07-0051A-060	6R3	
450	603	0053	ACS580MV-07-0053A-060	6R3	
500	671	0064	ACS580MV-07-0064A-060	6R4	
560	751	0072	ACS580MV-07-0072A-060	6R4	
630	845	0079	ACS580MV-07-0079A-060	6R4	
710	952	0088	ACS580MV-07-0088A-060	6R5	
800	1073	0098	ACS580MV-07-0098A-060	6R5	
900	1207	0105	ACS580MV-07-0105A-060	6R5	
1000	1341	0122	ACS580MV-07-0122A-060	6R6	
1120	1502	0137	ACS580MV-07-0137A-060	6R6	
1250	1676	0153	ACS580MV-07-0153A-060	6R6	
1400	1877	0169	ACS580MV-07-0169A-060	6R7	
1600	2146	0190	ACS580MV-07-0190A-060	6R7	
1800	2414	0205	ACS580MV-07-0205A-060	6R7	
2000	2682	0235	ACS580MV-07-0235A-060	6R8	
2250	3017	0263	ACS580MV-07-0263A-060	6R8	
2500	3353	0293	ACS580MV-07-0293A-060	6R8	
2800	3755	0328	ACS580MV-07-0328A-060	6R9	
3150	4224	0360	ACS580MV-07-0360A-060	6R9	
3550	4761	0410	ACS580MV-07-0410A-060	6R9	

Other ratings like 6.3 kV and 6.9 kV possible

Load profile 6.6 kV					
$U_N = 6.6 \text{ kV}$. The power ratings are valid at nominal voltage 6.6 kV.					
Normal use			Type designation	Frame size	
P_N (kW)	P_N (hp)	I_{2N} (A)			
250	335	0028	ACS580MV-07-0028A-066	6.6R1	
280	375	0031	ACS580MV-07-0031A-066	6.6R2	
315	422	0035	ACS580MV-07-0035A-066	6.6R2	
390	523	0042	ACS580MV-07-0042A-066	6.6R2	
450	603	0049	ACS580MV-07-0049A-066	6.6R3	
500	670	0055	ACS580MV-07-0055A-066	6.6R3	
580	777	0063	ACS580MV-07-0063A-066	6.6R4	
670	898	0073	ACS580MV-07-0073A-066	6.6R4	
750	1005	0082	ACS580MV-07-0082A-066	6.6R4	
800	1072	0087	ACS580MV-07-0087A-066	6.6R5	
900	1206	0098	ACS580MV-07-0098A-066	6.6R5	
1000	1340	0109	ACS580MV-07-0109A-066	6.6R5	
1150	1542	0125	ACS580MV-07-0125A-066	6.6R6	
1300	1743	0141	ACS580MV-07-0141A-066	6.6R6	
1500	2011	0163	ACS580MV-07-0163A-066	6.6R6	
1650	2212	0179	ACS580MV-07-0179A-066	6.6R7	
1800	2413	0195	ACS580MV-07-0195A-066	6.6R7	
2000	2681	0217	ACS580MV-07-0217A-066	6.6R7	
2250	3016	0244	ACS580MV-07-0244A-066	6.6R8	
2500	3351	0271	ACS580MV-07-0271A-066	6.6R8	
2700	3619	0293	ACS580MV-07-0293A-066	6.6R8	
3100	4155	0336	ACS580MV-07-0336A-066	6.6R9	
3600	4826	0390	ACS580MV-07-0390A-066	6.6R9	
4000	5362	0435	ACS580MV-07-0435A-066	6.6R9	

Nominal Ratings

P_N	Typical motor power at normal use
I_{2N}	Continuous current rating at 40 °C, allowing 110% I_{2N} for 1 min every 10 min

Load profile 10 kV **$U_N = 10$ kV. The power ratings are valid at nominal voltage 10 kV.**

Normal use			Type designation	Frame size
P_N (kW)	P_N (hp)	I_{2N} (A)		
225	302	0017	ACS580MV-07-0017A-100	10R1
250	335	0021	ACS580MV-07-0021A-100	10R1
280	375	0024	ACS580MV-07-0024A-100	10R1
355	476	0026	ACS580MV-07-0026A-100	10R1
400	536	0033	ACS580MV-07-0033A-100	10R2
450	603	0037	ACS580MV-07-0037A-100	10R2
500	671	0039	ACS580MV-07-0039A-100	10R2
560	751	0045	ACS580MV-07-0045A-100	10R3
630	845	0049	ACS580MV-07-0049A-100	10R3
710	952	0052	ACS580MV-07-0052A-100	10R3
800	1073	0062	ACS580MV-07-0062A-100	10R3
800	1073	0062	ACS580MV-07-0062A-100	10R4
900	1207	0069	ACS580MV-07-0069A-100	10R4
1000	1341	0075	ACS580MV-07-0075A-100	10R4
1120	1502	0082	ACS580MV-07-0082A-100	10R5
1250	1676	0091	ACS580MV-07-0091A-100	10R5
1400	1877	0102	ACS580MV-07-0102A-100	10R5
1600	2146	0116	ACS580MV-07-0116A-100	10R6
1800	2414	0130	ACS580MV-07-0130A-100	10R6
2000	2682	0143	ACS580MV-07-0143A-100	10R6
2250	3017	0156	ACS580MV-07-0156A-100	10R7
2500	3353	0176	ACS580MV-07-0176A-100	10R7
2800	3755	0197	ACS580MV-07-0197A-100	10R7
3150	4224	0219	ACS580MV-07-0219A-100	10R8
3550	4761	0247	ACS580MV-07-0247A-100	10R8
4000	5364	0278	ACS580MV-07-0278A-100	10R8
4500	6035	0310	ACS580MV-07-0310A-100	10R9
5000	6705	0340	ACS580MV-07-0340A-100	10R9
5600	7510	0387	ACS580MV-07-0387A-100	10R9

Other ratings like 10.5 kV possible

Load profile 11 kV **$U_N = 11$ kV. The power ratings are valid at nominal voltage 11 kV.**

Normal use			Type designation	Frame size
P_N (kW)	P_N (hp)	I_{2N} (A)		
250	335	0017	ACS580MV-07-0017A-110	11R1
280	375	0019	ACS580MV-07-0019A-110	11R1
315	422	0021	ACS580MV-07-0021A-110	11R1
385	516	0025	ACS580MV-07-0025A-110	11R1
450	603	0030	ACS580MV-07-0030A-110	11R2
510	684	0034	ACS580MV-07-0034A-110	11R2
585	784	0038	ACS580MV-07-0038A-110	11R2
630	845	0041	ACS580MV-07-0041A-110	11R3
710	952	0046	ACS580MV-07-0046A-110	11R3
800	1072	0052	ACS580MV-07-0052A-110	11R3
950	1273	0062	ACS580MV-07-0062A-110	11R4
1100	1475	0072	ACS580MV-07-0072A-110	11R4
1250	1676	0082	ACS580MV-07-0082A-110	11R4
1400	1877	0091	ACS580MV-07-0091A-110	11R5
1550	2078	0102	ACS580MV-07-0102A-110	11R5
1800	2413	0117	ACS580MV-07-0117A-110	11R6
2050	2748	0134	ACS580MV-07-0134A-110	11R6
2350	3150	0153	ACS580MV-07-0153A-110	11R6
2600	3485	0170	ACS580MV-07-0170A-110	11R7
2850	3820	0186	ACS580MV-07-0186A-110	11R7
3150	4223	0205	ACS580MV-07-0205A-110	11R7
3600	4826	0235	ACS580MV-07-0235A-110	11R8
4100	5496	0267	ACS580MV-07-0267A-110	11R8
4600	6166	0300	ACS580MV-07-0300A-110	11R8
5100	6836	0332	ACS580MV-07-0332A-110	11R9
5700	7641	0370	ACS580MV-07-0370A-110	11R9
6300	8445	0410	ACS580MV-07-0410A-110	11R9




Nominal ratings




P_N	Typical motor power at normal use
I_{2N}	Continuous current rating at 40 °C, allowing 110% I_{2N} for 1 min every 10 min

Standard interface and extensions for plug-in connectivity

The ACS580MV drives offer a wide range of standard interfaces. In addition, the drive has two option slots that can be used for extensions including fieldbus adapter modules and input/output extension modules.

Predefined macros enable easy and fast configuration of customer I/O's. ACS580MV offers following 3 macros and configurations as standard which support most frequently used application requirements like sequential control for retrofit.



Central Controller		
Default control connections for the factory macro		
XPOW	External power input	
1	+24 VI	24 V DC, 2 A (internally used)
2	GND	
XAI	Reference voltage and analog inputs	
1	+VREF	10 V DC, R_L 1...10 kohm
2	-VREF	-10 V DC, R_L 1...10 kohm
3	AGND	Ground
4	AI1+	Speed reference
5	AI1-	0 (2)...10 V, R_{in} > 200 kohm
6	AI2+	By default not in use
7	AI2-	0 (4)...20 mA, R_{in} > 100 ohm
XAO	Analog outputs	
1	AO1	Motor speed rpm
2	AGND	0...20 mA, R_L < 500 ohm
3	AO2	Motor current
4	AGND	0...20 mA, R_L < 500 ohm
XRO1	Relay outputs	
XRO2		
XRO3		
11	NC	 Ready 250 V AC/30 V DC 2 A
12	COM	
13	NO	
21	NC	 Running 250 V AC/30 V DC 2 A
22	COM	
23	NO	
31	NC	 Fault (-1) 250 V AC/30 V DC 2 A
32	COM	
33	NO	
XD24	Digital interlock	
5	+24 VD	+24 V DC 200 mA
6	DICOM	Digital input ground
7	+24 VD	+24 V DC 200 mA
8	DIOGND	Digital input/output ground
XDIO	Digital input/outputs	
1	DIO1	MCB trip command (internally used)
2	DIO2	MCB status closed (internally used)
XDI	Digital inputs	
1	DI1	Stop (0)/Start (1)
2	DI2	Forward (0)/Reverse (1)
3	DI3	Reset
4	DI4	Acc/Dec time set 1 (0)/set 2 (1)
5	DI5	Constant speed 1 (1 = On)
6	DI6	By default, not in use
X13	Control panel connection (internally used)	
X205	Memory unit connection (internally used)	
XETH	PC ethernet connection for Drive Composer	

Customer Interface Terminal Block		
X1	Customer Interface Terminal	
1		
3	MCB close cmd	Floating contacts to customer turn on/off current: 40 A
5		Thermal current: $I_{th} = 6 \text{ A}$ at 40 °C
7		Breaking capability:
9	MCB open cmd	AC-15 50 Hz I_e (240 V) = 4 A, I_e (500 V) = 2 A
11		DC-13 I_e (24 V) = 2.5 A, I_e (110 V) = 0.7 A, I_e (240 V) = 0.4 A
13		Minimum load: 17 V, 5 mA
15	MCB trip/unlock cmd	Isolation rated voltage 690 V AC
17		
19	MCB closed status	Connect contact from customer
21		Internal supply 24 V DC, 5 mA
23	MCB open status	Connect contact from customer
25		Internal supply 24 V DC, 20 mA, max resistance 140 ohm
27	MCB ready status	Connect contact from customer
29		Internal supply 24 V DC, 5 mA
31	Emergency off 1	Connect contacts from customer
33		Max resistance 60 ohm
35	Emergency off 2	Internal supply 24 V DC, 25 mA
37		
41	Remote MCB close cmd	Connect contacts from customer
43		Internal supply 24 V DC, 5 mA
45	Remote MCB open cmd	Switchable
47		
53	Alarm	RO, NC/NO can be selective, 250 V AC/30 V DC, 2 A
55		
57	Emergency off reset	To be determined
59		
61		
62		
63		
64	24 V DC	24 V DC for digit input
65		
66		
67		

Available macros for Central Controller

Hand/Auto macro (changes to factory macro)

XAI	Reference voltage and analog inputs	
4	AI1+	Speed reference (Hand)
5	AI1-	0(2)...10 V, $R_{in} > 200 \text{ kohm}$
6	AI2+	Speed reference (Auto)
7	AI2-	0(4)...20 mA, $R_L > 100 \text{ ohm}$
XDI	Digital inputs	
1	DI1	Stop (0)/Start (1) – Hand
2	DI2	Forward (0)/Reverse (1) – Hand
3	DI3	Hand (0)/Auto (1)
4	DI4	Constant speed 1 (1 = On)
5	DI5	Forward (0)/Reverse (1) – Auto
6	DI6	Stop (0)/Start (1) – Auto

PID control macro (changes to factory macro)

XAI	Reference voltage and analog inputs	
4	AI1+	Process or Speed reference
5	AI1-	0(2)...10 V, $R_{in} > 200 \text{ kohm}$
6	AI2+	Process feedback
7	AI2-	0(4)...20 mA, $R_L > 100 \text{ ohm}$
XDI	Digital inputs	
1	DI1	Stop (0)/Start (1) – Speed control
2	DI2	By default, not in use
3	DI3	Speed control (0)/Process control (1)
4	DI4	Constant speed 1 (1 = On)
5	DI5	Run enable (1 = On)
6	DI6	Stop (0)/Start (1) – Process control

Sequential control macro (changes to factory macro)

XAI	Reference voltage and analog inputs	
4	AI1+	External speed reference
5	AI1-	0(2)...10 V, $R_{in} > 200 \text{ kohm}$
6	AI2+	By default not in use
7	AI2-	0(4)...20 mA, $R_L > 100 \text{ ohm}$
XDI	Digital inputs	
1	DI1	Stop (0)/Start (1)
2	DI2	Forward (0)/Reverse (1)
3	DI3	Acc/Dec time set 1 (0)/set 2 (1)
4	DI4	
5	DI5	Constant speed selection max. 7 values
6	DI6	

Standard software with versatile features

Commissioning faster than ever before

The DriveStartup tool has a clear, intuitive and visually advanced interface as well as different assistants to make the drive simple to set up. This saves on commissioning time.

Sophisticated process control

The ACS580MV drives offer sophisticated process control in scalar and vector control modes for induction motors. Many embedded protection and other features improve performance of the motor and process.

Flying start

Flying start is available for both scalar and vector control modes. The drive catches a running motor which is often required in applications with long freewheeling times, such as in fan applications.

Load profile

The load profile feature collects drive values such as current to a log. The log shows how the drive is operating and enables you to analyze and optimize the application.

PID built-in

Built-in and stand-alone PID makes the ACS580MV a selfgoverning unit that requires no external logic input from the control room, but requires only an external process measurement.

Optimizing energy use

The ACS580MV drives come with features that help you save and manage energy. You can monitor the hourly, daily and cumulative energy consumption via kWh counters. When the drive replaces a direct-online control, you can follow the saved energy, CO₂ emissions or money, and see how fast the drive brings you a return on investment.

Easy diagnostics for trouble-free operation

The control panel's and Drive composer PC tool's diagnostics menu enables you to effectively analyze and resolve issues. You can quickly analyze why the drive is performing as it is; running, stopped or running at the preset speed. Active faults, warnings and event logs are shown in the menu. The menu shows if there are any active limitations to the drive operation and gives instructions on how to resolve them. The entry level drive composer PC tool is available for free via the ABB website.



Easy drive operation with Bluetooth control panel

Smooth navigation and process tuning

The control panel is equipped with context-sensitive soft keys and four-direction navigation enabling you to quickly browse and adjust the drive settings. Many flexible data visualizations including bar charts, histograms and trend



graphs help you analyze the process. With the panel's text editor, you can for example add information to I/O signals or customize fault and warning messages. You can also label the drive with a unique name.

Bluetooth control panel as standard

The standard control panel has a multilingual graphical display, Bluetooth connectivity and a USB interface for PC tool connection. The Bluetooth connection enables the use of mobile apps like Drivetune. This app is available for free on the Google Play and the Apple App store. Drivetune features include: commissioning, troubleshooting, monitoring and controlling the drive remotely.

Easy drive maintenance

Powerful backup and restore functions (with name, date and content) are supported as well as different language versions. Faults or warnings are quickly resolved as the help key provides context sensitive guidance and troubleshooting instructions.



PC tools for drive commissioning and process tuning capabilities

The free version of the Drive composer PC tool provides monitoring, commissioning and maintenance capabilities, while the professional version provides additional features such as custom parameter windows, control diagrams of the drive's configuration and improved monitoring and diagnostics.

The Drive composer tool is connected to the drive using the USB connection on the assistant control panel or an Ethernet connection on the drive. All drive information such as parameter loggers, faults, backups and event lists are gathered into a support diagnostics file. This provides faster fault tracking, shortens downtime and reduces operational and maintenance costs.

Drive composer pro offers extended functionality

Drive composer pro provides the same standard functionality as the free version, including parameter settings, downloading and uploading files and searching parameters. Advanced features such as graphical control diagrams and various displays are also available.

The control diagrams save users from browsing long lists of parameters and help to set the drive's logic quickly and easily. The tool has fast monitoring capabilities of multiple signals from several drives in a PC tool network. Full backup and restore functions are also included.

DriveStartup ensures fast and high quality commissioning

For the effortless drive commissioning the DriveStartup tool is applied. DriveStartup guides step by step through the complete commissioning including reporting and ensures highest quality, reduced commissioning time and therefore reduced costs.



Flexible connectivity to automation networks

A fieldbus enables communication between drives and PLC systems, I/O devices and the process. Fieldbus communication reduces wiring costs when compared with traditional hard wired input/output connections. Fieldbus systems also offer the ability to gather large amounts of data.

The general purpose drives are compatible with a wide range of fieldbus protocols. The optional plug-in fieldbus adapter modules can easily be mounted inside the drive.

The benefits of fieldbus communication are described below.

Drive monitoring

A set of drive parameters and/or actual signals, such as torque, speed, current, etc., can be selected for cyclic data transfer, providing fast data access.

Drive diagnostics

Accurate and reliable diagnostic information can be obtained through the alarm, limit and fault words, giving easy interfacing with plantwide HMIs.

Cabling

Substituting the large amount of conventional drive control cabling and wiring with a single cable reduces costs and increases system reliability and flexibility.

Design

The use of fieldbus control reduces engineering time at installation due to the modular structure of the hardware and software and the simplicity of the connections to the drives.

Universal communication with ABB fieldbus adapters

The ACS580MV supports the following fieldbus protocols:

Fieldbus adapter modules (2 slot available for I/O extension or fieldbus adapter)	
Fieldbus Adapter	Option
PROFIBUS-DP adapter	FPBA-01
Modbus adapter	FSCA-01
Ethernet adapter (EIP, Modbus/TCP, PROFINET)	FENA-11



Input/output extension modules for increased connectivity

Standard input and output can be extended by using optional analog and digital input/output extension modules. The modules are easily installed in the extension slots located on the main controller.

Typical functions like motor fan on/off can be easily configured by using FIO-11 and FIO-01 modules.

Analog and digital input/output extension modules	
Connections	Options
4 x DI/O, 2 x RO	FIO-01
3 x AI (mA/V), 1 x AO (mA), 2 x DI/O	FIO-11
2 x AI (mA/V), 2 x AO (mA)	FAIO-01

Cabinet options

The ACS580MV is available with IP42 protection class, thus ensuring reliable operation of the drive even under harsh environmental conditions.

As an option, the ACS580MV can be equipped with a cabinet heater that prevents humidity condensation inside the cabinet when the drive is not powered such as during plant maintenance or drive shut down time.

The optional low power auxiliary supply package does not require 380 V power supply and is the ideal solution in order to ensure safe line control power supply using customer UPS. This option is also available with a built-in UPS which is recommended in case of an unreliable auxiliary supply.

Cabinet option	Description
Drive cabinet and motor space heater	Additional external 220-240 V power supply required
Low power aux supply package	External single phase supply 100-240 V AC or 120-370 V DC, 3-phase fan supply from internal main transformer. Ideal for safe line control power supply.
Low power aux supply package + int. UPS	External single phase supply 100-240 V AC or 120-370 V DC and internal UPS (~10 min), 3-phase fan supply from internal main transformer. Ideal for high availability in case of unreliable auxiliary supply.

Cooling

The ACS580MV is fitted with cooling air fans. The cooling air must be free from corrosive materials, humidity and dust. The air temperature should not be above the maximum ambient temperature of 40 °C (50 °C with derating). Before installation please check the information in the technical data sheets.

Optional redundant cooling fans ensure an automatic switch to an additional fan in case

of cooling problems and guarantee highest reliability in the process operation. Furthermore, a special interface for the fan box is optional available in order to attach an air duct to the drive cabinet.

Cooling option
Redundant cooling fans
Fan box for air duct connection

Safety features

The integrated emergency off and emergency stop function means high safety for machine operators and is optionally available with SIL_{CL} 3/PL e certification.

Safety feature

Emergency Stop, Category 0 with opening main contactor/breaker (SIL_{CL} 3/PL e)

Manual bypass feature

Optional manual bypass minimizes unwanted process interruptions by connecting the system direct-on-line if needed. This feature provides additional risk management when retrofitting existing direct-on-line (DOL) systems with drives.



Specialities

Special environmental conditions and applications require a need-oriented selection and configuration of the drives. The ACS580MV offers a wide range of specialties which can be selected and might determine derating of the drive.

Different supply main voltage than drive output voltage is optionally available and covered by integrated step-up/down transformer. Extreme environmental conditions such as extended ambient temperature or a high altitude need special consideration when configuring the drive and may have an impact on the cabinet size.


Taking care of your drives, caring about your business

Whether a drive is a part of the product you sell or a component in your production process, reliable and efficient drive operation is key.

Our global life cycle services are designed to ensure that the drives keep running exactly as you expect, wherever they are. You will find support from your first meeting with ABB to the drive installation, commissioning and maintenance, all the way up to the eventual drive replacement and recycling. With a large number of offices around the world, we are well placed to offer you technical advice and local support.


Remote assistance

Should a fault be detected within a drive, ABB specialist provides rapid support by using the drive's data which is stored remotely. Remote assistance offers a cost-efficient way to identify and solve potential problems at your site, even in remote locations. The remote assistance is available 24/7 depending on your service contract.



Condition monitoring

Condition monitoring is a service that delivers you accurate, real-time information about drive events to ensure your equipment is available, reliable and maintainable. Via Customer Portal you can access live data, create customized reports and receive e-mail notifications of any drive faults or warnings.



Installation and commissioning

Through our global presence and international third party channel companies we offer accurate advice and timely support before and during installation. Our experienced engineers will optimize the drive performance to meet the precise demands of your application.

Technical support and training

ABB's experts are available 24/7 to offer fast and detailed technical advice to keep the customer's process or plant operational. This is supported by our online product manuals and technical support documentation. To complete our support we offer a broad portfolio of training and learning solutions designed to provide the customer with the knowledge to operate and maintain his drives.

Spare part packages

ACS580MV offers optional spare part packages for commissioning, 2 year and 5 year maintenance. It is delivered together with the drive and offers spare parts availability from day one. Inside the packages are all components included which may fail during installation due to misuse and which are required for regular maintenance of the drive for 2 or 5 year intervals.

Extended warranty

Our extended warranty reduces risks associated with drives failure and standard warranty terms and conditions are applied.

Service contracts

Service contracts and other type of agreements are available for your support, from individual service packages to complete drive care contracts covering all maintenance and repairs. ABB and its third party channel companies are able to tune the service contracts to satisfy your requirements.

Operation and maintenance

ABB has all options covered to keep your processes operational, from regular operation analyses and maintenance assessments to preventive maintenance and reconditioning of the drives. If a failure might occur ABB will guide you through a fast and efficient fault-finding procedure. Should corrective maintenance be needed ABB offers on-site and workshop repairs, fully backed up by a professional stock management ensuring availability and fast delivery of spare parts and exchange modules.

Spare parts and safety equipment	
Spare part kit	Description
Minimum – Commissioning spare part kit	Content see spare part kit list
Standard – Maintenance spare part kit 2 year	Content see spare part kit list
Extended – Maintenance spare part kit 5 year	Content see spare part kit list

A lifetime of peak performance

You're in control of every life cycle phase of your drives. At the heart of drive services is a four-phase product life cycle management model. This model defines the services recommended and available throughout drives lifespan.

Now it's easy for you to see the exact service and maintenance available for your drives.

ABB drives life cycle phases explained:

	Active	Classic	Limited	Obsolete
	Full range of life cycle services and support		Limited range of life cycle services and support	Replacement and end-of-life services
Product	Product is in active sales and manufacturing phase.	Serial production has ceased. Product may be available for plant extensions, as a spare part or for installed base renewal.	Product is no longer available.	Product is no longer available.
Services	Full range of life cycle services is available.	Full range of life cycle services is available. Product enhancements may be available through upgrade and retrofit solutions.	Limited range of life cycle services is available. Spare parts availability is limited to available stock.	Replacement and end-of-life services are available.

Keeping you informed
We notify you every step of the way using life cycle status statements and announcements.

Your benefit is clear information about your drives' status and precise services available. It helps you plan the preferred service actions ahead of time and make sure that continuous support is always available.

- Step 1**
Life Cycle Status Announcement
Provides early information about the upcoming life cycle phase change and how it affects the availability of services.
- Step 2**
Life Cycle Status Statement
Provides information about the drive's current life cycle status, availability of product and services, life cycle plan and recommended actions.



This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There is no text or other markings on the paper.



—

For more information, please contact
your local ABB representative or visit

abb.com/drives

abb.com/drivespartners



Zümrütevler Mh. Karayemiş Sk.,
REF PLAZA No:26 Kat:2 D:3
MALTEPE/İSTANBUL
Telefon : 444 3 168
E-Posta : info@borenerji.com